Creates list of users with given input array.

user · https://cbotai.shahrear.msf.bd/docs/creates-list-of-users-with-given-input-array/

POST `/user/createWithList`

Code Samples

```
curl --request POST \
  --url '/api/v3/user/createWithList' \
  --header 'Content-Type: application/json' \
  --data '[
    {
        "id": 10,
        "username": "theUser",
        "firstName": "John",
        "lastName": "James",
        "email": "john@email.com",
        "password": "12345",
        "phone": "12345",
        "userStatus": 1
    }
]'
```

```
const response = await fetch('/api/v3/user/createWithList', {
  method: 'POST',
  headers: {
    'Content-Type': 'application/json'
  },
  body: JSON.stringify([
    {
        "id": 10,
        "username": "theUser",
        "firstName": "John",
        "lastName": "James",
        "email": "john@email.com",
```

```
        "password": "12345",
        "phone": "12345",
        "userStatus": 1
    }
])
});

const data = await response.json();
console.log(data);
```

```
import requests

headers = {
    "Content-Type": "application/json"
}

payload = [
    {
        "id": 10,
        "username": "theUser",
        "firstName": "John",
        "lastName": "James",
        "email": "john@email.com",
        "password": "12345",
        "phone": "12345",
        "userStatus": 1
    }
]

response = requests.post("/api/v3/user/createWithList", headers=headers, json=payload)

print(response.json())
```

```
<?php
$curl = curl_init();

curl_setopt_array($curl, [
  CURLOPT_URL => '/api/v3/user/createWithList',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_CUSTOMREQUEST => 'POST',
```

```
  CURLOPT_HTTPHEADER => [
  'Content-Type: application/json'
  ],
  CURLOPT_POSTFIELDS => '[
    {
        "id": 10,
        "username": "theUser",
        "firstName": "John",
        "lastName": "James",
        "email": "john@email.com",
        "password": "12345",
        "phone": "12345",
        "userStatus": 1
    }
]',
]);

$response = curl_exec($curl);
curl_close($curl);

echo $response;
```

```
using System.Net.Http;
using System.Text;

var client = new HttpClient();
var request = new HttpRequestMessage(new HttpMethod("POST"), "/api/v3/user/createWithList");
request.Content = new StringContent(@"[
    {
        ""id"": 10,
        ""username"": ""theUser"",
        ""firstName"": ""John"",
        ""lastName"": ""James"",
        ""email"": ""john@email.com"",
        ""password"": ""12345"",
        ""phone"": ""12345"",
        ""userStatus"": 1
    }
]", Encoding.UTF8, "application/json");
var response = await client.SendAsync(request);
```

```
var body = await response.Content.ReadAsStringAsync();
Console.WriteLine(body);
```

```
import java.net.URI;
import java.net.http.*;

HttpClient client = HttpClient.newHttpClient();
HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("/api/v3/user/createWithList"))
    .header("Content-Type", "application/json")
    .method("POST", HttpRequest.BodyPublishers.ofString("""
[
    {
        "id": 10,
        "username": "theUser",
        "firstName": "John",
        "lastName": "James",
        "email": "john@email.com",
        "password": "12345",
        "phone": "12345",
        "userStatus": 1
    }
]
"""))
    .build();

HttpResponse<String> response = client.send(request, HttpResponse.BodyHandlers.ofString());
System.out.println(response.body());
```

Creates list of users with given input array.

Request Body

Content type: `application/json`

Field	Type	Required	Description
`[].id`	integer (int64)	Optional	
`[].username`	string	Optional	

Field	Type	Required	Description
`[].firstName`	string	Optional	
`[].lastName`	string	Optional	
`[].email`	string	Optional	
`[].password`	string	Optional	
`[].phone`	string	Optional	
`[].userStatus`	integer (int32)	Optional	User Status


```
[
    {
        "id": 10,
        "username": "theUser",
        "firstName": "John",
        "lastName": "James",
        "email": "john@email.com",
        "password": "12345",
        "phone": "12345",
        "userStatus": 1
    }
]
```


Responses

200 — Successful operation

Field	Type	Required	Description
`id`	integer (int64)	Optional	
`username`	string	Optional	
`firstName`	string	Optional	
`lastName`	string	Optional	

Field	Type	Required	Description
`email`	string	Optional	
`password`	string	Optional	
`phone`	string	Optional	
`userStatus`	integer (int32)	Optional	User Status


```
{
    "id": 10,
    "username": "theUser",
    "firstName": "John",
    "lastName": "James",
    "email": "john@email.com",
    "password": "12345",
    "phone": "12345",
    "userStatus": 1
}
```


default — Unexpected error

Response


```
200
{
    "id": 10,
    "username": "theUser",
    "firstName": "John",
    "lastName": "James",
    "email": "john@email.com",
    "password": "12345",
    "phone": "12345",
    "userStatus": 1
}
```