Delete a book

Books · https://cbotai.shahrear.msf.bd/docs/delete-a-book/

DELETE `/books/{bookid}`

Code Samples

```
curl --request DELETE \
  --url 'https://api.bookstore.example.com/v1/books/{bookid}' \
  --header 'X-API-Key: YOUR_API_KEY'
```

```
const response = await fetch('https://api.bookstore.example.com/v1/books/{bookid}', {
  method: 'DELETE',
  headers: {
    'X-API-Key': 'YOUR_API_KEY'
  }
});

const data = await response.json();
console.log(data);
```

```
import requests

headers = {
    "X-API-Key": "YOUR_API_KEY"
}

response = requests.delete("https://api.bookstore.example.com/v1/books/{bookid}", headers=headers)

print(response.json())
```

```
<?php
$curl = curl_init();
```

```
curl_setopt_array($curl, [
  CURLOPT_URL => 'https://api.bookstore.example.com/v1/books/{bookid}',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_CUSTOMREQUEST => 'DELETE',
  CURLOPT_HTTPHEADER => [
  'X-API-Key: YOUR_API_KEY'
  ],
]);

$response = curl_exec($curl);
curl_close($curl);

echo $response;
```

```
using System.Net.Http;

var client = new HttpClient();
var request = new HttpRequestMessage(new HttpMethod("DELETE"),
"https://api.bookstore.example.com/v1/books/{bookid}");
request.Headers.Add("X-API-Key", "YOUR_API_KEY");
var response = await client.SendAsync(request);
var body = await response.Content.ReadAsStringAsync();
Console.WriteLine(body);
```

```
import java.net.URI;
import java.net.http.*;

HttpClient client = HttpClient.newHttpClient();
HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.bookstore.example.com/v1/books/{bookid}"))
    .header("X-API-Key", "YOUR_API_KEY")
    .method("DELETE", HttpRequest.BodyPublishers.noBody())
    .build();

HttpResponse<String> response = client.send(request, HttpResponse.BodyHandlers.ofString());
System.out.println(response.body());
```

Remove A book from the catalog.

Path Parameters

Name	Type	Required	Description
`bookid`	string	**Required**	

Responses

200 — Successful response