Get a pet by ID

pets · https://cbotai.shahrear.msf.bd/docs/get-a-pet-by-id/

GET `/pets/{petId}`

Code Samples

```
curl --request GET \
  --url 'https://petstore.example.com/v1/pets/{petId}'
```

```
const response = await fetch('https://petstore.example.com/v1/pets/{petId}', {
  method: 'GET'
});

const data = await response.json();
console.log(data);
```

```
import requests

response = requests.get("https://petstore.example.com/v1/pets/{petId}")

print(response.json())
```

```
<?php
$curl = curl_init();

curl_setopt_array($curl, [
  CURLOPT_URL => 'https://petstore.example.com/v1/pets/{petId}',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_CUSTOMREQUEST => 'GET',
]);

$response = curl_exec($curl);
```

```
curl_close($curl);

echo $response;
```

```
using System.Net.Http;

var client = new HttpClient();
var request = new HttpRequestMessage(new HttpMethod("GET"),
"https://petstore.example.com/v1/pets/{petId}");
var response = await client.SendAsync(request);
var body = await response.Content.ReadAsStringAsync();
Console.WriteLine(body);
```

```
import java.net.URI;
import java.net.http.*;

HttpClient client = HttpClient.newHttpClient();
HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://petstore.example.com/v1/pets/{petId}"))
    .method("GET", HttpRequest.BodyPublishers.noBody())
    .build();

HttpResponse<String> response = client.send(request, HttpResponse.BodyHandlers.ofString());
System.out.println(response.body());
```

Path Parameters

Name	Type	Required	Description
`petId`	integer (int64)	**Required**	ID of the pet

Responses

200 — The pet

Field	Type	Required	Description

`name`	string	**Required**	
`tag`	string	Optional	
`id`	integer (int64)	**Required**	

```
{
    "name": "Mochi",
    "tag": "cat",
    "id": 1
}
```

404 — Pet not found

Response

```
200
{
    "name": "Mochi",
    "tag": "cat",
    "id": 1
}
```