Get user by user name.

user · https://cbotai.shahrear.msf.bd/docs/get-user-by-user-name/

GET `/user/{username}`

Code Samples

```
curl --request GET \
  --url '/api/v3/user/{username}'
```

```
const response = await fetch('/api/v3/user/{username}', {
  method: 'GET'
});

const data = await response.json();
console.log(data);
```

```
import requests

response = requests.get("/api/v3/user/{username}")

print(response.json())
```

```
<?php
$curl = curl_init();

curl_setopt_array($curl, [
  CURLOPT_URL => '/api/v3/user/{username}',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_CUSTOMREQUEST => 'GET',
]);

$response = curl_exec($curl);
curl_close($curl);
```

```
echo $response;
```

```
using System.Net.Http;

var client = new HttpClient();
var request = new HttpRequestMessage(new HttpMethod("GET"), "/api/v3/user/{username}");
var response = await client.SendAsync(request);
var body = await response.Content.ReadAsStringAsync();
Console.WriteLine(body);
```

```
import java.net.URI;
import java.net.http.*;

HttpClient client = HttpClient.newHttpClient();
HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("/api/v3/user/{username}"))
    .method("GET", HttpRequest.BodyPublishers.noBody())
    .build();

HttpResponse<String> response = client.send(request, HttpResponse.BodyHandlers.ofString());
System.out.println(response.body());
```

Get user detail based on username.

Path Parameters

Name	Type	Required	Description
`username`	string	**Required**	The name that needs to be fetched. Use user1 for testing

Responses

200 — successful operation

Field	Type	Required	Description
`id`	integer (int64)	Optional	

Field	Type	Required	Description
`username`	string	Optional	
`firstName`	string	Optional	
`lastName`	string	Optional	
`email`	string	Optional	
`password`	string	Optional	
`phone`	string	Optional	
`userStatus`	integer (int32)	Optional	User Status


```
{
    "id": 10,
    "username": "theUser",
    "firstName": "John",
    "lastName": "James",
    "email": "john@email.com",
    "password": "12345",
    "phone": "12345",
    "userStatus": 1
}
```


400 — Invalid username supplied

404 — User not found

default — Unexpected error

Response


```
200
{
    "id": 10,
    "username": "theUser",
```

```
    "firstName": "John",
    "lastName": "James",
    "email": "john@email.com",
    "password": "12345",
    "phone": "12345",
    "userStatus": 1
}
```