Subscribe to events

webhooks · https://cbotai.shahrear.msf.bd/docs/subscribe-to-events/

POST `/webhooks`

Code Samples

```
curl --request POST \
  --url 'https://api.taskflow.example.com/v2/webhooks' \
  --header 'Authorization: Bearer YOUR_TOKEN' \
  --header 'Content-Type: application/json' \
  --data '{
    "url": "https://example.com",
    "events": [
        "job.done"
    ]
}'
```

```
const response = await fetch('https://api.taskflow.example.com/v2/webhooks', {
  method: 'POST',
  headers: {
    'Authorization': 'Bearer YOUR_TOKEN',
    'Content-Type': 'application/json'
  },
  body: JSON.stringify({
    "url": "https://example.com",
    "events": [
        "job.done"
    ]
})
});

const data = await response.json();
console.log(data);
```

```
import requests

headers = {
    "Authorization": "Bearer YOUR_TOKEN",
    "Content-Type": "application/json"
}

payload = {
    "url": "https://example.com",
    "events": [
        "job.done"
    ]
}

response = requests.post("https://api.taskflow.example.com/v2/webhooks", headers=headers,
json=payload)

print(response.json())
```

```
<?php
$curl = curl_init();

curl_setopt_array($curl, [
  CURLOPT_URL => 'https://api.taskflow.example.com/v2/webhooks',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_HTTPHEADER => [
  'Authorization: Bearer YOUR_TOKEN',
  'Content-Type: application/json'
  ],
  CURLOPT_POSTFIELDS => '{
    "url": "https://example.com",
    "events": [
        "job.done"
    ]
}',
]);

$response = curl_exec($curl);
curl_close($curl);
```

```
echo $response;
```

```
using System.Net.Http;
using System.Text;

var client = new HttpClient();
var request = new HttpRequestMessage(new HttpMethod("POST"),
"https://api.taskflow.example.com/v2/webhooks");
request.Headers.Add("Authorization", "Bearer YOUR_TOKEN");
request.Content = new StringContent(@"{
    ""url"": ""https://example.com"",
    ""events"": [
        ""job.done""
    ]
}", Encoding.UTF8, "application/json");
var response = await client.SendAsync(request);
var body = await response.Content.ReadAsStringAsync();
Console.WriteLine(body);
```

```
import java.net.URI;
import java.net.http.*;

HttpClient client = HttpClient.newHttpClient();
HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.taskflow.example.com/v2/webhooks"))
    .header("Authorization", "Bearer YOUR_TOKEN")
    .header("Content-Type", "application/json")
    .method("POST", HttpRequest.BodyPublishers.ofString("""
{
    "url": "https://example.com",
    "events": [
        "job.done"
    ]
}
"""))
    .build();

HttpResponse<String> response = client.send(request, HttpResponse.BodyHandlers.ofString());
System.out.println(response.body());
```

Response

```
{
    "id": "123e4567-e89b-12d3-a456-426614174000",
    "url": "https://example.com",
    "events": [
        "string"
    ]
}
```

Request Body

Content type: `application/json` — **required**

Field	Type	Required	Description
`url`	string (uri)	**Required**	
`events`	array of string	**Required**	

```
{
    "url": "https://example.com",
    "events": [
        "job.done"
    ]
}
```

Responses

201 — Subscribed

Field	Type	Required	Description
`id`	string (uuid)	Optional	
`url`	string (uri)	Optional	

Field	Type	Required	Description
`events`	array of string	Optional	


```
{
    "id": "123e4567-e89b-12d3-a456-426614174000",
    "url": "https://example.com",
    "events": [
        "string"
    ]
}
```